



product *Specification*

#022

Solvent Based Carpet Seam Sealer



Capitol's 022 Solvent Based, Flammable Carpet Seam Sealer is specially formulated to prevent edge raveling and seal seams of most commercial and outdoor carpets. 022 is fast setting and water proof. 022 is compatible with most carpet backings. Do not use for sealing PVC backed

products, or products where seam sealers are not required. Excellent for direct glue and double glue applications.

Description: Solvent Based Carpet Seam Sealer

Flammability: Flammable

Clean Up: Safety solvent or mineral spirits.

Shelf Life: One year in closed container.

Limitations: Do not use for PVC or Vinyl Backed Products.

Packaging:

- 1 Quart (12/case)
- One Half Pint (12/case)

For The Installation Of:

- ActionBac®
- Jute
- Latex Unitary
- Wovens
- Rubber Backed
- Urethane (Attached Cushion)

Estimated Coverage:

- 160 lineal feet per 8 ounce bottle
- 2,560 lineal feet per gallon

Directions: Remove inner seal before using.
Application: Apply an 1/8" bead with dispenser tip at carpet primary backing and

immediately butt opposite cut. If carpet edges tend to peak, use board or weights to hold in place until dry. Adhesive may temporarily swell rubber back and cause a "peaking" effect - press down after allowing 30-60 minutes drying time. **CLEAN UP:** Use a safety solvent or mineral spirits. **DO NOT USE ON PVC BACKED CARPETS OR VINYL SHEET GOODS.**

First Aid: First Aid: Skin- Soap and water. Eyes- Flush with water, lifting upper and lower lids occasionally. Ingestion- Do not induce vomiting. Call physician or transport to an emergency facility. Inhalation- If affected, remove individual to fresh air. Use only in well ventilated areas.

Caution: FLAMMABLE! Use only in well ventilated areas. Do not use around sources of ignition such as open flames, pilot lights, etc. Do not store at temperatures above 120° F, or in direct sunlight. Do not incinerate container. Wrap empty container and put in trash collections. **KEEP OUT OF REACH OF CHILDREN**



Capitol USA, LLC
300 Cross Plains Blvd. • PO Box 2023
Dalton, GA 30722
800-831-8381 • Fax: 706-277-5753
Jim Walker ProSeries TechLine 888-234-8400
Website www.capitolusa.com

#022

Solvent Based Carpet Seam Sealer

SECTION I - PRODUCT IDENTIFICATION

Manufacturer's Name: Capitol USA, LLC
Address: 300 Cross Plains Blvd. • Dalton, GA 30720
Telephone #: 1-800-831-8381
Emergency Phone: 800-535-5053
Generic ID: Synthetic Rubber Adhesive in Solvent Solution
DOT Hazard Classification: Class 3 Flammable Liquid, UN1133
Product Identity: #022 Solvent Based Carpet Seam Sealer
HMIS: H=1 F=3 R=0

SECTION II - HAZARDOUS COMPONENTS

%(weight) PEL TLV
Lacolene 62.3 400 ppm 400 ppm (CAS# 64742-89-8)
Toluene 10.4 100 ppm 50 ppm (CAS# 108-88-3)
SARA TITLE III Reportable: Lacolene, Toluene

SECTION III - PHYSICAL DATA

Initial Boiling Point: 185°F - 220°F. Vapor Pressure: 38.0 mm Hg @ 68°F. Vapor Density (Air = 1.0 : 3.6). Specific Gravity: 0.71 @ 60°F. Percent Volatiles: 72.7%. G/L VOC (Calculated): 553.0.

SECTION IV - FIRE AND EXPLOSION DATA

Flash Point: 20°F - 32°F. Explosive Limit (Product): 1.2%. Extinguishing Media: Foam, CO₂, Dry Chemical. HAZARDOUS DECOMPOSITION PRODUCTS: May form toxic materials: carbon dioxide and carbon monoxide, various hydrocarbons of unknown structure. SPECIAL FIRE FIGHTING PROCEDURES: Water may be used to keep fire-exposed containers cool until fire is out. Wear self-contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode when fighting fires. UNUSUAL FIRE & EXPLOSION HAZARDS: Never use welding or cutting torch on or near cans (even empty) because resultant pressure could rupture. Empty cans should be incinerated.

SECTION V - HEALTH HAZARD DATA

Permissible Exposure Level: 400 ppm. Threshold Limit Value: 400 ppm. EFFECTS OF EXPOSURE: Eyes- Can cause irritation, redness, tearing, blurred vision. Skin- Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis. Breathing- Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, and even asphyxiation. First Aid: Skin- Soap and water. Eyes- Flush with water, lifting upper and lower lids occasionally. Ingestion- Do not induce vomiting. Call physician or transport to an emergency facility. Inhalation- If affected, remove individual to fresh air. Use only in well ventilated areas.

SECTION VI - REACTIVITY DATA

Stability: Stable. Incompatibility: None. Hazardous Decomposition: None. Hazardous Polymerization: Can not Occur. Conditions To Avoid: Strong Oxidizing Agents, Open Flame, and Excessive Heat

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb liquid on paper, vermiculite, floor absorbent, or other absorbent material and transfer to hood. Allow volatile portion to evaporate in hood. Allow sufficient time for vapors to completely clear hood duct work. Dispose of remaining material in accordance with applicable regulations.

SECTION VIII - PROTECTIVE EQUIPMENT

VENTILATION: Adequate ventilation is essential to prevent vapor build-up. Open all available windows and entrances to insure good ventilation. RESPIRATORY PROTECTION: Adequate ventilation is normally sufficient. If eyes begin to water or dizziness or head aches are experienced, increase fresh air supply, wear an NIOSH approved respirator, or leave the area. PROTECTIVE GLOVES: Wear protective gloves to prevent skin contact. EYE PROTECTION: Wear glasses or protective goggles to avoid splashes. OTHER PROTECTIVE EQUIPMENT: None required. WASH HANDS THOROUGHLY WITH SOAP AND WATER.

SECTION IX - SPECIAL PRECAUTIONS

Protect from freezing. Use only in applications as stated on the label. Do not take internally. Close container after each use. Avoid skin and eye contact. Extinguish any open flames, sparks, or other sources of ignition. Keep away from excessive heat.

Ventilation with fresh air, including open doors and windows should be observed during any flooring installation. Operate HVAC systems at 100% fresh air intake before, during and after installation to eliminate lingering odors or particulate matter. KEEP OUT OF REACH OF CHILDREN

Capitol USA believes the data set forth herein is accurate as of the date hereof, and makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.

Capitol USA, LLC
300 Cross Plains Blvd. • PO Box 2023
Dalton, GA 30722
800-831-8381 • Fax: 706-277-5753
Jim Walker ProSeries TechLine 888-234-8400
Website www.capitolusa.com